

Focus Mini

FO-MAA23W - 3000 K - Optics $38^{\circ} / 3 \text{ W} / 3000 \text{ K} / \text{CRI} > 90$

DESCRIPTION


The recessed downlight Focus range are designed to be used for accent lighting in small and medium spaces. Small in size but great performance, they are proposed in different sizes and powers. The choice between MICRO, MINI, MEDIUM and BIG allows the use of the appliance that best suits your needs. Our range include fix and adjustable versions. All models can be configured by color choice, product color and management (On/Off, DALI, Push, Phase Cut). Opticts with different beam angle can be selected. LED is placed in the back position and characterizes the product for remarcable cut off. The product is made of aluminium turning and presente simplified installation. Different colors available in the Focus range: in addition to black and white you can choose tobacco, sand and silver. The driver is separate from the product, our proposal include several power supply in reason of the installation.



Switch On÷Off

PRODUCTS CHARACTERISTICS

Recessed Spotlights installation type material Aluminum Color White 3 W Power 144 lm Lumen output - Full emission 48 lm/W Efficacy ø 28 mm. Diameter **Dimensions** h 45 mm. 0,049 kg. net weight



ELECTRICAL CHARACTERISTICS

driver On÷Off

MECHANICAL CHARACTERISTICS

product IP rate IP20



Focus Mini

FO-MAA23W - 3000 K - Optics 38° / 3 W / 3000 K / CRI >90

HOLE RECESS DIMENSIONS

hole recess diameter ø 25 mm.

LED SOURCE DETAILS

led source type Power Led

Photobiological risk RG 1 Low risk (IEC 62471)

LED current 700 mA
Light temperature 3000 K
CRI CRI >90
SDCM <3

DRIVER CHARACTERISTICS

driver On÷Off

LIGHTING DETAILS

luminous effect spot optic 38°
Beam angle – direct 38°

PHOTOMETRIC

